

Correction

Correction: Halil, B.; Gökhan, S. Numerical Investigation of the Effect of Variable Baffle Spacing on the Thermal Performance of a Shell and Tube Heat Exchanger. *Energies* 2017, 10, 1156

Halil Bayram ^{1,2} and Gökhan Sevilgen ^{1,*}

¹ Department of Automotive Engineering, Faculty of Engineering, Uludağ University, Görükle, Bursa 16059, Turkey; halilbayram@uludag.edu.tr or halil.bayram@amasya.edu.tr

² Department of Automotive Engineering, Faculty of Technology, Amasya University, Amasya 05100, Turkey

* Correspondence: gsevilgen@uludag.edu.tr; Tel.: +90-224-294-2648

Received: 30 November 2017; Accepted: 4 December 2017; Published: 20 December 2017

The authors wish to make the following corrections to this paper [1]:
On page 3, Equation (8) should be changed from:

$$\text{Nu} = \frac{(f/2) \cdot \text{Re} \cdot \text{Pr}}{1.07 \times 12.7 \times (f/2)^2 \times (\text{Pr}^{0.66} - 1)} \quad (8)$$

to the following correct version:

$$\text{Nu} = \frac{(f/2) \cdot \text{Re} \cdot \text{Pr}}{1.07 + 12.7 \cdot (f/2)^{1/2} \cdot (\text{Pr}^{2/3} - 1)} \quad (8)$$

The authors would like to apologize for any inconvenience caused to the readers by these changes.

Reference

1. Halil, B.; Gökhan, S. Numerical Investigation of the Effect of Variable Baffle Spacing on the Thermal Performance of a Shell and Tube Heat Exchanger. *Energies* 2017, 10, 1156. [[CrossRef](#)]



© 2017 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).