

Supplementary Materials

Design of a Waterborne Polyurethane–Urea Ink for Direct Ink Writing 3D Printing

Julen Vadillo ^{1,2}, Izaskun Larraza ¹, Tamara Calvo-Correas ¹, Nagore Gabilondo ¹, Christophe Derail ^{2,*} and Arantxa Eceiza ^{1,*}

¹ Materials + Technologies Research Group (GMT), Department of Chemical and Environmental Engineering, Faculty of Engineering of Gipuzkoa, University of Basque Country, Plz. Europa 1, 20018 Donostia-San Sebastian, Spain; julen.vadillo@univ-pau.fr (J.V.); izaskun.larraza@ehu.eus (I.L.); tamara.calvo@ehu.eus (T.C.-C.); nagore.gabilondo@ehu.eus (N.G.)

² E2S UPPA, IPREM, UMR5254, Centre National de la Recherche Scientifique (CNRS), Institut des Sciences Analytiques & de PhysicoChimie pour l'Environnement & les Matériaux, Université de Pau et Pays de l'Adour, 64000 Pau, France

* Correspondence: christophe.derail@univ-pau.fr (C.D.); arantxa.eceiza@ehu.eus (A.E.)




Figure S1. Adjustment to the Herschel-Bulkley model of WBPUU29 flow curve.




Figure S2. G' (■) and G'' (□) as a function of strain ($T = 22.5\text{ }^{\circ}\text{C}$) of WBPUU inks with different solid content at 1Hz.