

Supplementary Data

Total Meniscus Reconstruction Using a Hybrid-Scaffold: Combined with 3D-printed Biomimetic Framework and Micro-Particle

Hun-Jin Jeong^{1,#}, Se-Won Lee^{2,#}, Myoung Wha Hong³, Young Yul Kim³, Kyoung Duck Seo^{1,*}, Young-Sam Cho^{1,4,*} and Seung-Jae Lee^{1,4,*}

¹Department of Mechanical Engineering, College of Engineering, Wonkwang University, 460 Iksandae-ro, Iksan, Jeonbuk, 54538, Republic of Korea


²Department of Orthopedics, Seoul St. Mary's Hospital, Catholic University of Korea, 10, 63-ro, Yeongeungpo-gu, Seoul, 07345, Republic of Korea

³Department of Orthopedics, Daejeon St. Mary's Hospital, Catholic University of Korea, 64, Daeheung-ro, Jung-gu, Daejeon, 34943, Republic of Korea


⁴Department of Mechanical and Design Engineering, College of Engineering, Wonkwang University, 460 Iksandae-ro, Iksan, Jeonbuk, 54538, Republic of Korea

[#]These authors contributed equally to this work.

*Co-correspondence to K.D.S (kdseo85@wku.ac.kr), Y.-S. C (youngsamcho@wku.ac.kr) and S.-J. L. (sjlee411@wku.ac.kr)



Supplemental Figure S1. Fabrication process of the biomimetic 3D-printed hybrid scaffold



Supplemental Figure S2. Surgical procedure for hybrid-scaffolds, 1) anchored to medial aspects of the proximal tibia and midbody portion nearest from the MCL tibial for 2) fixation of hybrid-scaffold.