
Supplementary Materials

Influence of Rare Earth Oxide Concentration on Electrochemical Co-deposition of Nd and Pr from NdF₃-PrF₃-LiFBased Melts

Vesna S. Cvetković ^{1,*}, Dominic Feldhaus ², Nataša M. Vukićević ¹, Ksenija Milicevic-Neumann ², Tanja S. Barudžija ³, Bernd Friedrich ² and Jovan N. Jovićević ¹

¹ Department of Electrochemistry, Institute of Chemistry, Technology and Metallurgy, National Institute of the Republic of Serbia, University of Belgrade, 110000 Belgrade, Serbia; vukicevic@ihtm.bg.ac.rs (N.M.V.); jovicevic@ihtm.bg.ac.rs (J.N.J.)

² IME Process Metallurgy and Metal Recycling, Institute of RWTH Aachen University, 52056 Aachen, Germany; dfeldhaus@metallurgie.rwth-aachen.de (D.F.); kmneumann@metallurgie.rwth-aachen.de (K.M.-N.); bfriedrich@metallurgie.rwth-aachen.de (B.F.)

³ Institute for Nuclear Sciences Vinča, University of Belgrade, 11001 Belgrade, Serbia; tbarudzija@vin.bg.ac.rs

* Correspondence: v.cvetkovic@ihtm.bg.ac.rs




Figure S1. (a) SWVs obtained with different frequencies on W working electrode: pulse height: 25 mV; potential step: 1 mV; Variation of the peak current density vs. the square root of the frequency for: (b) Peak II; (c) Peak III. Electron transfer numbers were calculated based on the half-peak width recorded by SWV (embedded in the picture).