

Supplementary Materials

Preparation and Characterization of Screen-Printed Cu₂S/PEDOT:PSS Hybrid Films for Flexible Thermoelectric Power Generator

Junmei Zhao ¹, Xiaolong Zhao ¹, Rui Guo ², Yixin Zhao ², Chenyu Yang ^{1,2}, Liping Zhang ¹, Dan Liu ^{1,2,*} and Yifeng Ren ^{1,*}

¹ School of Electrical and Control Engineering, North University of China, Taiyuan 030051, China; zhaojunmei@nuc.edu.cn (J.Z.); zhaoxiaolong@nuc.edu.cn (X.Z.); yangwangcgsa@163.com (C.Y.); zhangliping@nuc.edu.cn (L.Z.)

² Key Laboratory of Instrumentation Science & Dynamic Measurement, Ministry of Education, North University of China, Taiyuan 030051, China; 18406589626@163.com (R.G.); zhaoyaxinnuc@163.com (Y.Z.)

* Correspondence: liudan235@nuc.edu.cn (D.L.); renyifeng@nuc.edu.cn (Y.R.)




Figure S1. The cross-sections of (a) P1.1, (b) P1.2, (c) P1.3, and (d) P1.4 films.




Figure S2. Element mapping diagram of P1.2 film, (a) SEM diagram of P1.2 film, (b) C element, (c) O element, (d) S element, (e) Cu element.



Figure S3. The image of the P1.1 film module no longer adheres to the PI substrate.