

Low-Cost Arduino Reverse Transcriptase Loop-Mediated Isothermal Amplification (RT-LAMP) for Sensitive Nucleic Acid Detection

Bruno Dias Camargo ^{1,2}, Mateus Cassaboni Stracke ^{1,2}, Heloisa Bruna Soligo Sanchuki ¹, Viviane Klassen de Oliveira ², Hellen Cristina Ancelmo ^{1,2}, Dayanne Mozaner Bordin ^{3,*}, Fabricio Klerynton Marchini ^{1,2}, Emilson Ribeiro Viana ⁴ and Lucas Blanes ^{1,2}

- ¹ Laboratory for Applied Science and Technology in Health, Carlos Chagas Institute, Oswaldo Cruz Foundation (Fiocruz), Professor Algacyr Munhoz Mader 3775 St., Curitiba 81350-010, Brazil; bruno.camargo@ibmp.org.br (B.D.C.); mateus.stracke@ibmp.org.br (M.C.S.); heloisa.sanchuki@ibmp.org.br (H.B.S.S.); hellen.ancelmo@ibmp.org.br (H.C.A.); fabricio.marchini@ibmp.org.br (F.K.M.); lucas.blanes@fiocruz.br (L.B.)
- ² Paraná Institute of Molecular Biology, Professor Algacyr Munhoz Mader 3775 St., Curitiba 81350-010, Brazil; klassen.viviane@gmail.com
- ³ School of Mathematical and Physical Sciences, Faculty of Science, University of Technology Sydney, Ultimo, NSW 2007, Australia
- ⁴ Academic Department of Physics (DAFIS), Federal University of Technology – Paraná (UTFPR), Sete de Setembro 3165 Av., Curitiba 80230-901, Brazil; emilsonjunior@utfpr.edu.br
- * Correspondence: dayanne.bordin@uts.edu.au

Supplementary Table S1. Set of RT-LAMP primers originally designed by Rabe and Cepko (2020) to detect SARS-CoV-2 by RT-LAMP and presently used by our research group.

Primers	Sequence (5' - 3')
F3	CGGTGGACAAATTGTCAC
B3	CTTCTCTGGATTTAACACACTT
LF	TTACAAGCTTAAAGAATGTCTGAACACT
LB	TTGAATTTAGGTGAAACATTTGTCACG
FIP	TCAGCACACAAAGCCAAAAATTTATTTTTCTGTGCAAAGGAAATTAAGGAG
BIP	TATTGGTGGAGCTAAACTTAAAGCCTTTTCTGTACAATCCCTTTGAGTG