

Melamine-Modified Graphene Oxide as a Corrosion Resistance Enhancing Additive for Waterborne Epoxy Resin Coatings

Xin Li ¹, Dongsheng Li ², Jie Chen ¹, Dongxia Huo ¹, Xin Gao ¹, Junhui Dong ², Yue Yin ¹, Jun Liu ^{2,*} and Ding Nan ^{1,2,*}

¹ College of Chemistry and Chemical Engineering, Inner Mongolia University, Hohhot 010021, China; lx_imu@126.com (X.L.); cj_imu@163.com (J.C.); hdx_imu@163.com (D.H.); gaoxinxixin@163.com (X.G.); yinyue@imu.edu.cn (Y.Y.)

² Inner Mongolia Key Laboratory of Graphite and Graphene for Energy Storage and Coating, School of Materials Science and Engineering, Inner Mongolia University of Technology, Hohhot 010051, China; 20181100167@imut.edu.cn (D.L.); jhdong@imut.edu.cn (J.D.)

* Correspondence: clxylj@163.com (J.L.); nd@imu.edu.cn (D.N.)

List

Figure S1. FT-IR spectra of GO and MGO.

Figure S2. FT-IR spectra of GO and MGO (5:1), and local magnified views

Figure S3. Raman spectra of GO and MGO.

Figure S4. XRD spectra of GO and MGO.

Figure S5. Photograph of coating adhesion test.




Figure S1. FT-IR spectra of GO and MGO.




Figure S2. FT-IR spectra of GO and MGO (5:1), and local magnified views




Figure S3. Raman spectra of GO and MGO.




Figure S4. XRD spectra of GO and MGO.




Figure S5. Photograph of coating adhesion test. (scale bar: 1 cm)