


Article

Impact Responses and Parameters Sensitivity Analysis of Electric Wheelchairs

Song Wang , Leilei Zhao *, Yanzhu Hu and Fuxing Yang

School of Automation, Beijing University of Posts and Telecommunications, 10 Xitucheng Road, Haidian District, Beijing 100876, China; wongsangwongsang@163.com (S.W.); yzhu@263.net (Y.H.); yangfx@bupt.edu.cn (F.Y.)

* Correspondence: zhaoleilei611571@163.com; Tel.: +86-181-0125-5891

Received: 8 May 2018; Accepted: 1 June 2018; Published: 3 June 2018



Featured Application: This work is specifically applied to wheelchairs.

Abstract: The shock and vibration of electric wheelchairs undergoing road irregularities is inevitable. The road excitation causes the uneven magnetic gap of the motor, and the harmful vibration decreases the recovery rate of rehabilitation patients. To effectively suppress the shock and vibration, this paper introduces the DA (dynamic absorber) to the electric wheelchair. Firstly, a vibration model of the human-wheelchair system with the DA was created. The models of the road excitation for wheelchairs going up a step and going down a step were proposed, respectively. To reasonably evaluate the impact level of the human-wheelchair system undergoing the step-road transition, evaluation indexes were given. Moreover, the created vibration model and the road-step model were validated via tests. Then, to reveal the vibration suppression performance of the DA, the impact responses and the amplitude frequency characteristics were numerically simulated and compared. Finally, a sensitivity analysis of the impact responses to the tire static radius r and the characteristic parameters was carried out. The results show that the DA can effectively suppress the shock and vibration of the human-wheelchair system. Moreover, for the electric wheelchair going up a step and going down a step, there are some differences in the vibration behaviors.

Keywords: electric wheelchairs; step road excitation; impact responses; sensitivity analysis

1. Introduction

Wheelchairs are medical devices [1]. They are widely used in hospitals, rehabilitation institutions, and endowment institutions [2]. With the progress of society, rehabilitation wheelchairs have developed from simple travel tools to important means of enabling the elderly and the disabled to exercise, take care of themselves, and participate in social activities [3–5]. They have played an important role in integrating the elderly and the disabled back into society.

Wheelchairs can be mainly divided into three categories according to their sophistication: manual wheelchairs [6], electric wheelchairs [7], and intelligent wheelchairs [8]. Manual wheelchairs are the most common rehabilitation accessories. They have been widely used by the elderly and the disabled. Manual wheelchairs are affordable and more suitable for ordinary families. Electric wheelchairs are based on the traditional manual wheelchairs. They are equipped with a high-performance power driving device, batteries, and an electric control system [9]. A traditional wheelchair must rely on manpower. If no one takes care of the user, he/she will have to push the wheel himself. For an electric wheelchair, so long as the batteries are fully charged, there is no need for the family members to accompany the user all of the time. Intelligent wheelchairs are an important application platform of robot technologies. They combine many technologies in the robot field, such as motion control,

machine vision, pattern recognition, and human–machine interaction [10,11]. The price of intelligent wheelchairs is very high. It is difficult for ordinary families to afford them.

In recent years, the enormous demand for wheelchairs has led to higher performance requirements [12]. How to effectively reduce the shock and vibration of electric wheelchairs has aroused a growing public attention [13–15]. When an electric wheelchair undergoes road irregularities, the shock and vibration of the human body and the wheelchair body are inevitable. The adverse effects of the shock and vibration caused by the road excitation mainly include four aspects. (1) The shock and vibration transmitted to the human body decrease the recovery rate of the patients. (2) The road excitation causes the uneven magnetic gap of the motor, resulting in the further deterioration of the vibration. (3) The intense shock causes a shorter working life of the wheelchair accessories, which include for instance, the mechanical parts, the motor, and the control hardware system. (4) The excessive vibration reduces the tire grounding safety.

Various standards have been developed around the world to evaluate the performances of wheelchairs. The British standard 12183-2009 provides the requirements and the test methods of manual wheelchairs [16]. America instituted the standard ANSI/RESNA WC-1a-2009 for wheelchairs [17]. China instituted the standard GB/T 13800-2009 [18]. This standard is applicable for manual wheelchairs and electric wheelchairs. Generally speaking, the vibration acceleration of the human body is used to evaluate the ride comfort of wheelchairs; the vibration acceleration of the wheelchair body is used to evaluate the operational reliability of the wheelchair accessories. Moreover, the tire dynamic deflection f_d or the tire contact force is often used to characterize the tire grounding safety [19].

To effectively reduce the shock and vibration of wheelchairs, scholars from various countries have studied the issue and made some achievements. Some scholars focused on the investigation of the cushion system of wheelchairs. For example, Hillman et al. investigated the hysteresis and impact damping of cushions for wheelchairs [20]. Wang et al. studied the comfort of cushions for electric wheelchairs [21]. Brienza et al. researched the influences of the wheelchair cushion type on tissue deformation [22]. Some scholars paid attention to the dynamic modeling of wheelchairs. For example, Brown et al. created a model of wheelchair-users undergoing vibrations [23]. Leary et al. proposed a mathematical model of wheelchair biomechanics [24]. Chen et al. established a model of an electric wheelchair and identified its system parameters [25]. Salipur et al. developed a rear impact model of an adult manual transit wheelchair with a seated occupant [26]. Ceravolo et al. created a predictive control model of an autonomous wheelchair [27]. These models provide useful references and tools for analyzing the comfort and vibration of wheelchairs. In addition, there are also some scholars who devoted themselves to the vibration characteristics research of wheelchairs. Dziechciowski et al. analyzed the vibration transmitted to the human body during the patient's ride in a wheelchair [28]. Hikmawan et al. analyzed the comfort of electric wheelchairs using a half-car model [29]. Miyawaki et al. studied the whole-body vibration of passengers sitting on wheelchairs loaded onto a lifter [30]. Su et al. designed a magnetic suspension vibrator for electric wheelchairs [31]. Ababou et al. developed a test bench for the analysis of harmful vibrations to wheelchair users [32]. Hischke et al. analyzed the influence of the rear wheel suspension on the tilt-in-space wheelchair shock and vibration attenuation [33]. These studies provide useful references for attenuating the shock and vibration of wheelchairs. However, there are few studies on the comprehensive performance of wheelchairs undergoing a step.

The dynamic absorber (DA) is a vibration-reducing device that is connected to the vibration system by elastic and damping elements. It occupies a small space, and provides a cheap and effective way to attenuate the shock and vibration of various vibration systems [34]. For example, Orečný et al. introduced the DA to a working machine seat, and showed that the DA can effectively suppress the seat vibration [35]. However, there have been no related research reports on the use of dynamic absorbers in wheelchairs. To effectively suppress the shock and vibration, this paper introduces the DA to the electric wheelchair. In Section 2, to theoretically prove the vibration isolation effect of the DA in

wheelchairs, a vibration model of the human-wheelchair system with the DA was created. In Section 3, the models of the road excitation for wheelchairs going up a step and going down a step were proposed, respectively. In Section 4, to effectively evaluate the impact level of the human-wheelchair system undergoing the step road, the evaluation indexes were given. In Section 5, the created vibration model and the road step model were validated by test. In Section 6, to reveal the vibration suppression performance of the DA, the impact responses were numerically simulated and compared. In Section 7, the influences of the tire static radius r on the vibration behaviors of the human-wheelchair system were analyzed. In Section 8, the influences of the characteristic parameters on the vibration behaviors were revealed.

2. Modeling of the Human-Wheelchair System with DA

A commercially available electric wheelchair is shown in Figure 1a. According to the electric wheelchair, a simplified vibration model of the human-wheelchair system with the DA was created, as shown in Figure 1b where the motor is fixed on the wheelchair body; m_2 , m_1 , and m_0 are the human body mass, the wheelchair body mass (including the motor mass), and the DA mass, respectively; C_2 and C_0 are the damping coefficients of the cushion and the DA, respectively; K_2 , K_1 , and K_0 are stiffness coefficients of the cushion, the tire system, and the DA, respectively; z_2 , z_1 , and z_0 are the corresponding displacements; and q is the road excitation.




Figure 1. The electric wheelchair: (a) a commercial product; (b) the vibration model.

The differential equations of the vibration model can be expressed as:

$$\begin{cases} m_2 \ddot{z}_2 + C_2(\dot{z}_2 - \dot{z}_1) + K_2(z_2 - z_1) = 0 \\ m_0 \ddot{z}_0 + C_0(\dot{z}_0 - \dot{z}_1) + K_0(z_0 - z_1) = 0 \\ m_1 \ddot{z}_1 + C_2(\dot{z}_1 - \dot{z}_2) + K_2(z_1 - z_2) + C_0(\dot{z}_1 - \dot{z}_0) + K_0(z_1 - z_0) + K_1(z_1 - q) = 0 \end{cases} \quad (1)$$

The natural frequencies, the damping ratios, and other ratio parameters have important guiding significances for the wheelchair design. The characteristic parameters are adopted as follows:

$$\omega_2 = \sqrt{\frac{K_2}{m_2}}, \omega_1 = \sqrt{\frac{K_1}{m_1}}, \omega_0 = \sqrt{\frac{K_0}{m_0}}, \zeta_2 = \frac{C_2}{2\sqrt{m_2 K_2}}, \zeta_0 = \frac{C_0}{2\sqrt{m_0 K_0}}, r_0 = \frac{m_0}{m_1}, r_2 = \frac{m_2}{m_1}$$

where, ω_0 , ω_1 , and ω_2 are the natural circular frequencies of the DA, the wheelchair body, and the human body, respectively; ζ_0 and ζ_2 are the damping ratios of the DA system and the cushion system, respectively; r_0 is the mass ratio of the DA mass to the wheelchair body mass; and r_2 is the mass ratio of the human body mass to the wheelchair body mass.

Based on the adopted characteristic parameters, Equation (1) can be rewritten as:

$$\begin{cases} m_2 \ddot{z}_2 + 2m_2 \xi_2 \omega_2 (\dot{z}_2 - \dot{z}_1) + m_2 \omega_2^2 (z_2 - z_1) = 0 \\ m_0 \ddot{z}_0 + 2m_0 \xi_0 \omega_0 (\dot{z}_0 - \dot{z}_1) + m_0 \omega_0^2 (z_0 - z_1) = 0 \\ m_1 \ddot{z}_1 + 2m_2 \xi_2 \omega_2 (\dot{z}_1 - \dot{z}_2) + m_2 \omega_2^2 (z_1 - z_2) + 2m_0 \xi_0 \omega_0 (\dot{z}_1 - \dot{z}_0) + m_0 \omega_0^2 (z_1 - z_0) + m_1 \omega_1^2 (z_1 - q) = 0 \end{cases} \quad (2)$$

Equation (2) can be further expressed as:

$$\begin{cases} \ddot{z}_2 + 2\xi_2 \omega_2 (\dot{z}_2 - \dot{z}_1) + \omega_2^2 (z_2 - z_1) = 0 \\ \ddot{z}_0 + 2\xi_0 \omega_0 (\dot{z}_0 - \dot{z}_1) + \omega_0^2 (z_0 - z_1) = 0 \\ \ddot{z}_1 + 2r_2 \xi_2 \omega_2 (\dot{z}_1 - \dot{z}_2) + r_2 \omega_2^2 (z_1 - z_2) + 2r_0 \xi_0 \omega_0 (\dot{z}_1 - \dot{z}_0) + r_0 \omega_0^2 (z_1 - z_0) + \omega_1^2 (z_1 - q) = 0 \end{cases} \quad (3)$$

3. Modeling of the Step Road Excitation

When a wheelchair goes up a step or goes down a step, the displacement excitation is not exactly the same as the step shape. The tire has a correction to the step-road surface. Figure 2 depicts the rolling condition of the tire passing the step without leaving the road surface. In Figure 2, the dotted line is the trajectory of the tire center; r is the static radius of the tire; h is the height of the step; and δ is the horizontal distance of the tire center to the step.




Figure 2. The step-road surface.

From Figure 2, we obtain the following:

$$\delta^2 + (r - h)^2 = r^2. \quad (4)$$

Based on Equation (4), we produce:

$$\delta = \sqrt{2rh - h^2}. \quad (5)$$

For a wheelchair going up the step, the step-road excitation can be expressed as:

$$q = \begin{cases} h + \sqrt{r^2 - (\delta - vt)^2} - r & t \in [0, \frac{\delta}{v}] \\ h & t \in (\frac{\delta}{v}, +\infty] \end{cases}, \quad (6)$$

where t is time, and v is the running speed of wheelchairs.

For a wheelchair going down the step, the step road excitation can be expressed as:

$$q = \begin{cases} \sqrt{r^2 - v^2 t^2} - r & t \in [0, \frac{\delta}{v}] \\ -h & t \in (\frac{\delta}{v}, +\infty] \end{cases}. \quad (7)$$

For example, $r = 250$ mm for a wheelchair, $h = 35$ mm, and $v = 0.4, 0.8$, and 1.2 m/s. Figure 3a,b depicts the time histories of the step excitation q for the wheelchair going up the step and going down the step, respectively. It can be seen that the greater the running speed v , the more sharply the excitation changes.




Figure 3. The time histories of the step excitation q for the wheelchair: (a) going up the step; and (b) going down the step.

4. Evaluation Indexes

In order to evaluate the impact level of the human-wheelchair system undergoing the step road, the unweighted vibration dose values (VDV) of the wheelchair body and the human body are adopted, respectively. They are the cumulative values of the corresponding acceleration values for a period of time. According to the ISO2631 standard, the sensitivity of the human body to different vibration frequencies is different. When evaluating the impact of the vibration on the human health, the vibration signals need to be weighted on the basis of the ISO2631 standard. This study mainly focuses on the impact strength and analyzes the vibration isolation effect of the DA. Thus, the acceleration signals are not weighted.

Based on the vibration model, the vibration dose value VDV_1 of the wheelchair body acceleration $\ddot{z}_1 = a_1$ can be expressed as:

$$VDV_1 = \left[\int_0^T a_1^4(t) dt \right]^{\frac{1}{4}}. \quad (8)$$

where T is the length of time from the tire starting to contact the step to the vibration disappearing.

The vibration dose value VDV_2 of the human body acceleration $\ddot{z}_2 = a_2$ can be expressed as:

$$VDV_2 = \left[\int_0^T a_2^4(t) dt \right]^{\frac{1}{4}}. \quad (9)$$

The boundary condition of the tires off the ground can be expressed as:

$$f_d - f_{d0} \geq 0. \quad (10)$$

For the human-wheelchair system with the DA and without the DA, the calculation formula of the tire static deflection f_{d0} are as follows, respectively:

$$f_{d0} = \begin{cases} \frac{m_0 + m_1 + m_2}{K_1}, & \text{with DA} \\ \frac{m_1 + m_2}{K_1}, & \text{without DA} \end{cases}, \quad (11)$$

The ratio p of the length of time for $f_d - f_{d0} \geq 0$ to T is adopted as the evaluation index of the running safety:

$$p = \frac{N\Delta t}{T}, \quad (12)$$

where N is the number of the points satisfying Equation (10); and Δt is the simulation step.

When the wheelchair undergoes a step, during the time from the tire starting to contact the step to the vibration disappearing, the condition of the tire off the ground should be avoided. If the tire does not contact the ground, the maneuverability of the wheelchair will be reduced. Thus, the smaller of the ratio p , the better the tire grounding safety.

In order to further investigate the vibration attenuation effect of the DA, the vibration transfer characteristics need to be analyzed. According to Equation (3), the transfer functions of the wheelchair body acceleration \ddot{z}_1 , the human body acceleration \ddot{z}_2 , and the tire dynamic deflection $f_d = z_1 - q$ to the road excitation velocity \dot{q} can be respectively expressed as:

$$H_1 = H_{\ddot{z}_1 \sim \dot{q}} = \frac{\omega_1^2 s^5 + (2\xi_0\omega_0 + 2\xi_2\omega_2)\omega_1^2 s^4 + (\omega_0^2 + 4\xi_0\xi_2\omega_0\omega_2 + \omega_2^2)\omega_1^2 s^3 + L_X s^2 + \omega_0^2\omega_1^2\omega_2^2 s}{s^6 + L_5 s^5 + L_4 s^4 + L_3 s^3 + L_2 s^2 + L_1 s + L_0}, \quad (13)$$

$$H_2 = H_{\ddot{z}_2 \sim \dot{q}} = \frac{2\xi_2\omega_1^2\omega_2 s^4 + (\omega_2^2 + 4\xi_0\xi_2\omega_0\omega_2)\omega_1^2 s^3 + L_X s^2 + \omega_0^2\omega_1^2\omega_2^2 s}{s^6 + L_5 s^5 + L_4 s^4 + L_3 s^3 + L_2 s^2 + L_1 s + L_0}, \quad (14)$$

$$H_3 = H_{f_d \sim \dot{q}} = \frac{\omega_1^2 s^4 + 2(\xi_0\omega_0 + \xi_2\omega_2)\omega_1^2 s^3 + (\omega_0^2 + 4\xi_0\xi_2\omega_0\omega_2 + \omega_2^2)\omega_1^2 s^2 + L_X s + \omega_0^2\omega_1^2\omega_2^2}{(s^6 + L_5 s^5 + L_4 s^4 + L_3 s^3 + L_2 s^2 + L_1 s + L_0)s} - \frac{1}{s}, \quad (15)$$

where s is the Laplace operator:

$$L_X = 2(\xi_2\omega_0^2\omega_2 + \xi_0\omega_0\omega_2^2)\omega_1^2,$$

$$L_5 = 2\xi_0\omega_0 + 2\xi_2\omega_2 + 2\xi_0\omega_0r_0 + 2\xi_2\omega_2r_2,$$

$$L_4 = \omega_0^2 + \omega_1^2 + \omega_2^2 + r_0\omega_0^2 + r_2\omega_2^2 + 4\xi_0\xi_2\omega_0\omega_2 + 4r_0\xi_0\xi_2\omega_0\omega_2 + 4r_2\xi_0\xi_2\omega_0\omega_2,$$

$$L_3 = 2\xi_0\omega_0\omega_1^2 + 2\xi_0\omega_0\omega_2^2 + 2\xi_2\omega_0^2\omega_2 + 2\xi_2\omega_1^2\omega_2 + 2r_0\xi_0\omega_0\omega_2^2 + 2r_0\xi_2\omega_0^2\omega_2 + 2r_2\xi_0\omega_0\omega_2^2 + 2r_2\xi_2\omega_0^2\omega_2,$$

$$L_2 = \omega_0^2\omega_1^2 + \omega_0^2\omega_2^2 + \omega_1^2\omega_2^2 + r_0\omega_0^2\omega_2^2 + r_2\omega_0^2\omega_2^2 + 4\xi_0\xi_2\omega_0\omega_1^2\omega_2,$$

$$L_1 = 2\xi_0\omega_0\omega_1^2\omega_2^2 + 2\xi_2\omega_0^2\omega_1^2\omega_2, L_0 = \omega_0^2\omega_1^2\omega_2^2.$$

5. Test Verification

To verify the effectiveness of the created vibration model and the step road model, the test verification should be carried out. If the DA system is directly mounted on electric wheelchairs, there will be some risks. For example, the mismatched DA may aggravate the vibration of wheelchairs and do harm to human bodies. Therefore, this study carried out the pulse test by using an electric wheelchair manufactured by Bo Yu Electric Vehicle Co., Ltd. (Yongkang, China). This wheelchair is not equipped with the DA system. The values of the parameters for the human-wheelchair system are shown in Table 1.

Table 1. The values of the parameters for the human-wheelchair system.

Parameter	Value	Parameter	Value
m_2 (kg)	75	K_2 (N/mm)	11.84
m_1 (kg)	25	K_1 (N/mm)	98.70
C_2 (Ns/m)	377	r (mm)	250

The pulse test was conducted in the test field, as shown in Figure 4a. The height of the step is $h = 35$ mm. The test condition is $v = 0.2\sim 0.8$ m/s. The test equipment is LMS Test.Lab (LMS Company, Leuven, Belgium), as shown in Figure 4b. The sample frequency was set as 512 Hz. Before the test, a Lance LC0173 acceleration sensor (Lance Technologies Inc., Copley, OH, America) was installed on the cushion of the test wheelchair, as shown in Figure 4c.




Figure 4. Pulse test: (a) the test field; (b) the test equipment LMS Test.Lab; (c) the set up of the test.

The tested values of VDV_2 were calculated based on the measured human body acceleration signals. Moreover, according to the parameters in Table 1, the simulated human body acceleration signals were obtained using Equation (1) with $m_0 = 0$. Then, the simulated values of VDV_2 were calculated. Tables 2 and 3 give the comparisons of the calculated results. From tables 2 and 3, it can be seen that the relative deviations of the simulated VDV_2 and the tested VDV_2 are less than 10%. The results show that the created vibration model for the wheelchair without the DA is workable, and the step road model is effective.

Table 2. A comparison of the calculated values of vibration dose values (VDV_2) for the wheelchair going up the step.

Running Speed v (m/s)	The Tested VDV_2 ($ms^{-1.75}$)	The Simulated VDV_2 ($ms^{-1.75}$)	The Relative Deviation (%)
0.2	0.70	0.74	5.7
0.4	1.48	1.42	5.1
0.6	1.90	1.97	3.7
0.8	2.25	2.36	4.9

Table 3. A comparison of the calculated values of VDV_2 for the wheelchair going down the step.

Running Speed v (m/s)	The Tested VDV_2 ($ms^{-1.75}$)	The Simulated VDV_2 ($ms^{-1.75}$)	The Relative Deviation (%)
0.2	0.71	0.69	2.8
0.4	1.45	1.40	3.4
0.6	1.76	1.67	4.0
0.8	2.10	1.92	8.6

6. Comparison Analysis of Performances

6.1. The Time Domain Responses

To reveal the vibration suppression performance of the DA, the impact responses were numerically simulated. The simulation condition is set as: $h = 35$ mm, $v = 0.2\sim 1.2$ m/s. The simulation step is set as $\Delta t = 0.001$ s. Table 4 gives the values of the parameters for the human-wheelchair system. Based on the selection method of the DA [34,35], the DA mass m_0 was selected as the 10% of the wheelchair body mass m_1 . To make $\omega_0 = \omega_1$, the DA stiffness K_0 was also selected as the 10% of the tire stiffness K_1 . The damping ratio ζ_0 was selected as 0.25; thus, $C_0 = 78$ Ns/m. Figure 5 provides a comparison of the vibration behaviors of the human-wheelchair system with the DA and without the DA undergoing the step.

Table 4. The values of the parameters for the human-wheelchair system.

Parameter	Value	Parameter	Value
m_2 (kg)	75	K_2 (N/mm)	11.84
m_1 (kg)	25	K_1 (N/mm)	98.70
m_0 (kg)	2.5	K_0 (N/mm)	9.87
C_2 (Ns/m)	377	r (mm)	250
C_0 (Ns/m)	78		




Figure 5. A comparison of the vibration behaviors of the human-wheelchair system with the dynamic absorber (DA) and without the DA undergoing the step: (a) VDV_1 versus v ; (b) VDV_2 versus v ; (c) p versus v .

As shown in Figure 5a, VDV_1 increases linearly with the increase of the running speed v . The curves of VDV_1 versus v are almost the same for the wheelchair going up and going down the step. Compared with the wheelchair without the DA, the VDV_1 of the wheelchair with the DA is reduced by 11.2%. Figure 5b shows that VDV_2 increases nonlinearly with the increase of the running speed v . The VDV_2 values of the wheelchair going down the step are slightly larger than those of the wheelchair going up the step. Compared with the wheelchair without the DA, the VDV_2 of the wheelchair with the DA is reduced by 11.3%. As shown in Figure 5c, p increases rapidly with the increase of the running speed v at the beginning. When $v > 0.8$ m/s, p hardly increases. From $v = 0.0$ m/s to $v = 0.4$ m/s, the DA system has little effect on p . When $v = 0.8$ m/s, the improvement of p is up to 16.7%. In addition, the curves of p versus v are almost the same from $v = 0.0$ m/s to $v = 0.4$ m/s for the wheelchair going up and going down the step. When $v > 0.4$ m/s, the p value of the wheelchair going down the step is obviously larger than that of the wheelchair going up the step.

The comparison results show that the three evaluation indexes are all improved by using the DA. This proves that the DA can effectively improve the vibration isolation performance of the wheelchairs. In addition, when the wheelchair goes up the step and goes down the step, the differences for VDV_1 and VDV_2 are relatively smaller, but the differences for p are relatively larger, with a maximum difference of more than 10%.

To more clearly show the effects of the DA for the wheelchair undergoing the step, Figures 6–8 give a comparison of the time histories of the vibration responses. As shown in Figure 6a,b, compared with the wheelchair without the DA, the wheelchair with the DA can rapidly attenuate the road impact. When the wheelchair goes up the step, the maximum acceleration of the wheelchair body appears during the process of the wheelchair going up the step. When the wheelchair goes down the step, the maximum acceleration of the wheelchair body appears after passing the step. Figure 7a,b shows that the DA can only significantly reduce the second maximum peak of the human body acceleration.

The maximum acceleration of the human body for the wheelchair going up the step is 26.6% larger than that for the wheelchair going down the step. Figure 8a,b indicates that the DA can effectively suppress f_d starting from the second peak. In the process of the wheelchair going up the step, the maximum value of f_d is reduced by 33.4% by using the DA. The maximum value of f_d cannot be obviously improved in the process of the wheelchair going down the step.




Figure 6. A comparison of the time histories of the wheelchair body acceleration a_1 for the system with the DA and without the DA: (a) going up the step; (b) going down the step.




Figure 7. A comparison of the time histories of the human body acceleration a_2 for the system with the DA and without the DA: (a) going up the step; (b) going down the step.




Figure 8. A comparison of the time histories of the tire dynamic deflection f_d for the system with the DA and without the DA: (a) going up the step; (b) going down the step.

6.2. The Frequency Responses

Only analyzing the time domain responses is not enough to fully reveal the differences of the system with the DA and without the DA. The amplitude frequency characteristics of the system should be analyzed. In this section, based on the parameters in Table 1, the curves of $|H_1|$, $|H_2|$, and $|H_3|$ versus the excitation frequency f were plotted, as shown in Figure 9.

Figure 9a shows that the amplitude of $|H_1|$ for the system with the DA is 38.5% smaller than that for the system without the DA in the resonant region of the wheelchair body. The result proves that the DA can effectively suppress the vibration of the wheelchair body. Figure 9b depicts that by using the DA, the amplitude of $|H_2|$ can be reduced about 23.5% around the second resonance peak. The result proves that although the DA cannot suppress the vibration of the human body around the first resonance peak, it can obviously improve the vibration isolation performance of the wheelchair system around the second resonance peak. From Figure 9c, it can be seen that the maximum amplitude of $|H_3|$ appears in the resonant region of the wheelchair body; the amplitude is reduced by more than 20.0% in this region. To sum up, the DA can significantly reduce the amplitudes of $|H_1|$, $|H_2|$, and $|H_3|$ in the resonant region of the wheelchair body. Moreover, the DA does not lead to the vibration deterioration in the resonant region of the human body. The DA has a favorable effect that reduces the tire dynamic deflection and attenuates the vibration of the human body and the wheelchair body.




Figure 9. A comparison of the amplitude frequency characteristics of the system with the DA and without the DA: (a) $|H_1|$ for the wheelchair versus f ; (b) $|H_2|$ for the human versus f ; (c) $|H_3|$ for the tire versus f .

7. Influences of the Tire Static Radius r on the Vibration Behaviors

To reveal the influences of the tire static radius r on the vibration behaviors, the impact responses were numerically simulated for $r = 200$ mm, 250 mm, and 300 mm, respectively. The used parameters of the human-wheelchair system with the DA are in Table 4. The simulation condition is set as: $h = 35$ mm,

$v = 0.5$ m/s. The simulation step is set as $\Delta t = 0.001$ s. The calculated results of the vibration responses were given in Table 5. The comparisons of the time histories of the wheelchair body acceleration a_1 , the human body acceleration a_2 , and the tire dynamic deflection f_d at different values of r are shown in Figures 10–12, respectively

Table 5. The calculated results of the vibration responses.

r (mm)	VDV ₁ (ms ^{−1.75})		VDV ₂ (ms ^{−1.75})		p (%)	
	Up	Down	Up	Down	Up	Down
200	5.56	5.66	1.86	1.71	7.48	7.68
250	4.87	4.94	1.70	1.58	7.46	5.64
300	4.39	4.46	1.57	1.49	7.35	5.62




Figure 10. A comparison of the time histories of the wheelchair body acceleration a_1 at different values of r for the wheelchair: (a) going up the step; (b) going down the step.




Figure 11. A comparison of the time histories of the human body acceleration a_2 at different values of r for the wheelchair: (a) going up the step; (b) going down the step.




Figure 12. A comparison of the time histories of the human body acceleration a_2 at different values of r for the wheelchair: (a) going up the step; (b) going down the step.

Table 5 shows that with the increase of the tire static radius r , the vibration responses VDV_1 , VDV_2 , and p decrease. Thus, increasing r contributes to the attenuation of the pavement impact. Figure 10a,b shows that increasing r can effectively suppress the vibration peaks of the wheelchair body acceleration a_1 . Interestingly, with the increase of r , the response curve of a_1 clearly moves to the right for the wheelchair going down the step. Figure 11a,b illustrates that increasing r helps to reduce the vibration of the human body. Similarly, with the increase of r , the response curve of a_2 also moves to the right for the wheelchair going down the step. Figure 12a depicts that increasing r cannot obviously reduce the maximum value of f_d for the wheelchair going up the step. Figure 12b shows that increasing r can effectively reduce the maximum value of f_d for the wheelchair going down the step. Moreover, the response curve of f_d also shifts to the right.

8. Sensitivity Analysis of the Impact Responses to the Characteristic Parameters

To reveal the influence laws of the characteristic parameters r_2 , r_0 , ξ_2 , ξ_0 , f_1 , f_2 , and f_0 on the vibration behaviors, VDV_1 , VDV_2 , and p were calculated. Where, $f_0 = \omega_0/2\pi$, $f_1 = \omega_1/2\pi$, and $f_2 = \omega_2/2\pi$. When analyzing the influence of one of the seven characteristic parameters, the baseline value is increased by 100% or decreased by 50%. The values of the characteristic parameters are provided in Table 6. To plot the curves of VDV_1 , VDV_2 , and p versus a certain characteristic parameter in one diagram, VDV_1 , VDV_2 , and p are normalized by $y_1 = VDV_1/|VDV_1|_b$, $y_2 = VDV_2/|VDV_2|_b$, and $y_3 = p/|p|_b$, respectively, where, the subscript “b” represents “baseline”.

Table 6. The values of the characteristic parameters.

Characteristic Parameter	Baseline	+100%	−50%
r_2	3.0	6.0	1.5
r_0	0.10	0.05	0.20
ξ_2	0.25	0.5	0.125
ξ_0	0.25	0.5	0.125
f_2	2.0	4.0	1.0
f_1	10.0	20.0	5.0
f_0	10.0	20.0	5.0

8.1. Influences of the Mass Ratios r_0 and r_2

Figures 13 and 14 show the curves of the evaluation indexes y_1 , y_2 , and y_3 versus the mass ratios r_0 and r_2 , respectively. As shown in Figure 13, the effect of r_0 on y_2 is very small. With the increase of r_0 , both y_1 and y_3 decrease. For the wheelchair going up the step, r_0 has a greater influence on y_1 than on y_3 . For the wheelchair going down the step, r_0 has a greater influence on y_3 than on y_1 . Therefore,

it is difficult to effectively suppress the vibration acceleration of the human body by changing r_0 . From Figure 14, it can be seen that the change trends of y_i versus r_2 are similar for the wheelchair going up and going down the step, while y_1 and y_2 are in inverse proportion to r_2 . Therefore, increasing r_2 is beneficial to suppress the vibration of the human body and the wheelchair body, but it also reduces the running safety.




Figure 13. The evaluation index y_i versus the mass ratio r_0 for the wheelchair: (a) going up the step; (b) going down the step.




Figure 14. The evaluation index y_i versus the mass ratio r_2 for the wheelchair: (a) going up the step; (b) going down the step.

8.2. Influences of the Damping Ratios ζ_0 and ζ_2

Figures 15 and 16 show the curves of the evaluation indexes y_1 , y_2 , and y_3 versus the damping ratios of ζ_0 and ζ_2 , respectively. By comparing Figure 15a,b, it can be seen that the trends are similar, but there are also some subtle differences. For the wheelchair going up the step, y_3 is almost proportional to ζ_0 . However, with the increase of ζ_0 , y_3 nonlinearly increases. Reducing ζ_0 helps to effectively improve the running safety. It can also be seen that y_1 and y_2 are not sensitive to the damping ratio ζ_0 . Figure 16a,b shows that an optimal value of ζ_2 exists to minimize y_2 ; ζ_2 has a greater influence on y_3 , but it has little effect on y_1 and y_2 . Increasing ζ_2 helps to improve the running safety and reduce the road impact.




Figure 15. The evaluation index y_i versus the DA system damping ratio ζ_0 for the wheelchair: (a) going up the step; (b) going down the step.




Figure 16. The evaluation index y_i versus the cushion system damping ratio ζ_2 for the wheelchair: (a) going up the step; (b) going down the step.

8.3. Influences of the Natural Frequencies f_0 , f_1 , and f_2

Figures 17–19 show the curves of the evaluation indexes y_1 , y_2 , and y_3 versus the natural frequencies f_0 , f_1 , and f_2 , respectively.




Figure 17. The evaluation index y_i versus the natural frequency f_0 for the wheelchair: (a) going up the step; (b) going down the step.




Figure 18. The evaluation index y_i versus the natural frequency f_1 for the wheelchair: (a) going up the step; (b) going down the step.




Figure 19. The evaluation index y_i versus the natural frequency f_2 for the wheelchair: (a) going up the step; (b) going down the step.

For the wheelchair going up the step, with the increase of f_0 , both y_2 and y_3 decrease firstly and then increase; however, y_2 increases continuously, as shown in Figure 17a. For the wheelchair going down the step, with the increase of f_0 , y_1 , y_2 , and y_3 decrease firstly and then increase, as shown in Figure 17b. y_1 is very sensitive to f_1 , as shown in Figure 18. Thus, reducing f_1 can help to reduce the impact of the road to the wheelchair body. As can be seen in Figure 18, f_1 has a minimal effect on y_2 . From Figure 19, it can be seen that y_1 , y_2 , and y_3 are very sensitive to f_2 ; y_1 is inversely proportional to f_2 ; both y_2 and y_3 are approximately proportional to f_2 .

8.4. Sensitivity Calculation of the Vibration Responses

Based on the influence trends analysis of the characteristic parameters on the vibration responses y_i , the sensitivity values were calculated. Table 7 provides the calculated results. The calculation formulae are as follows:

$$\begin{cases} s_{yi} = \frac{y(U_i + \Delta U_i) - y(U_i)}{y(U_i)} / \frac{\Delta U_i}{U_i} \\ s_y = \sqrt{\frac{1}{n} \sum_{i=1}^n |s_{yi}|^2} \end{cases}, \quad (16)$$

where n is the number of the intervals, i represents the i th interval; ΔU_i refers to the incremental value of the characteristic parameter U in the i th interval; s_y is the response sensitivity; and y represents VDV_1 , VDV_2 , and p .

Table 7. The calculated results of the vibration response sensitivity.

System Parameter	S_{VDV_1}		S_{VDV_2}		S_p	
	Up	Down	Up	Down	Up	Down
r_0	0.258	0.281	0.001	0.091	0.191	0.345
r_2	0.521	0.532	0.305	0.232	0.500	0.606
ξ_0	0.090	0.065	0.050	0.078	0.230	0.178
ξ_2	0.454	0.440	0.354	0.457	0.907	0.780
f_0	0.227	0.187	0.112	0.155	0.365	0.277
f_1	1.095	1.101	0.256	0.183	0.531	0.773
f_2	0.556	0.561	1.011	1.087	0.922	0.914

From Table 7, it can be seen that the sensitivity values are not exactly the same for the wheelchair going up the step and going down the step. In both cases, VDV_1 is the most sensitive to f_1 , and other influencing factors from strong to weak are f_2 , r_2 , ξ_2 , r_0 , f_0 , and ξ_0 . In both cases, VDV_2 is the most sensitive to f_2 and other influencing factors of VDV_2 from strong to weak are ξ_2 , r_2 , f_1 , f_0 , ξ_0 , and r_0 . p is very sensitive to both ξ_2 and f_2 . For the wheelchair going up the step, other influencing factors from strong to weak are f_1 , r_2 , f_0 , ξ_0 , and r_0 . However, for wheelchair going down the step, other influencing factors of VDV_2 from strong to weak are f_1 , r_2 , r_0 , f_0 , and ξ_0 .

9. Conclusions

This paper introduces the DA to the electric wheelchair. A vibration model of the human-wheelchair system with the DA was created. Models of the road excitation for wheelchairs going up a step and going down a step were proposed, respectively. The vibration dose value VDV_1 of the wheelchair body acceleration a_1 , the vibration dose value VDV_2 of the human body acceleration a_2 , and the time ratio p were adopted as evaluation indexes of the vibration behaviors. The impact responses and the amplitude frequency characteristics were numerically simulated and compared. The influences of the tire static radius r and the characteristic parameters on the vibration behaviors were revealed. The results of this study demonstrate the following:

- (1) The three evaluation indexes are all improved by using the DA. When the wheelchair goes up the step and goes down the step, the differences for VDV_1 and VDV_2 are relatively smaller, but the differences for p are relatively larger.
- (2) The DA can significantly reduce the amplitudes of $|H_1|$, $|H_2|$, and $|H_3|$ in the resonant region of the wheelchair body. Moreover, the DA does not lead to the vibration deterioration in the resonant region of the human body. The DA has the favorable effect of reducing the tire dynamic deflection and attenuating the vibration of the human body and the wheelchair body.
- (3) With the increase of the tire static radius r , the vibration responses VDV_1 , VDV_2 , and p decrease. Thus, increasing r contributes to the attenuation of the pavement impact. The sensitivity values of the vibration responses to the characteristic parameters are not exactly the same for the wheelchair going up the step and going down the step. In both cases, VDV_1 is the most sensitive to f_1 , and VDV_2 is the most sensitive to f_2 . Meanwhile, p is very sensitive to both ξ_2 and f_2 .

The contribution of the experiment to the validation of the model is obviously limited; the model of the human-wheelchair system with the DA should be validated by test for further research. Moreover, the selection and matching of the DA should be discussed in detail.

Author Contributions: The corresponding author L.Z. proposed this research; L.Z. and S.W. performed the simulation; Y.H. and L.Z. analyzed the data; F.Y. reviewed and edited the manuscript; S.W. wrote the paper.

Funding: This work is supported by National Natural Science Foundation of China (No. 61627816), the National Key R&D Program of China (No. 2016YFC0701309).

Conflicts of Interest: The authors declare no conflict of interest.

References

- Kim, K.T.; Suk, H.I.; Lee, S.W. Commanding a brain-controlled wheelchair using steady-state somatosensory evoked potentials. *IEEE Trans. Neural Syst. Rehabil. Eng.* **2018**, *26*, 654–665. [[CrossRef](#)] [[PubMed](#)]
- Gong, D.X.; He, R.; Zuo, G.Y.; Yu, J.Y. Motion mapping in the joint space for the control of the heterogeneous wheelchair-mounted robotic arm. *Acta Electron. Sin.* **2018**, *46*, 464–472.
- Nguyen, V.T.; Jayawardena, C.; Ardekani, I. A navigation model for side-by-side robotic wheelchairs for optimizing social comfort in crossing situations. *Robot. Auton. Syst.* **2018**, *100*, 27–40. [[CrossRef](#)]
- Travlos, V.; Patman, S.; Wilson, A. Quality of life and psychosocial well-being in youth with neuromuscular disorders who are wheelchair users: A systematic review. *Arch. Phys. Med. Rehabil.* **2016**, *98*, 1004–1017. [[CrossRef](#)] [[PubMed](#)]
- Wu, B.F.; Chen, P.Y.; Lin, C.H. A New criterion of human comfort assessment for wheelchair robots by Q-Learning based accompanist tracking fuzzy controller. *Int. J. Fuzzy Syst.* **2016**, *18*, 1039–1053. [[CrossRef](#)]
- Routhier, F.; Lettre, J.; Miller, W.C.; Borisoff, J.F.; Keetch, K. Data logger technologies for manual wheelchairs: A scoping review. *Assist. Technol.* **2018**, *30*, 51–58. [[CrossRef](#)] [[PubMed](#)]
- Rojas, M.; Ponce, P.; Molina, A. A fuzzy logic navigation controller implemented in hardware for an electric wheelchair. *Int. J. Adv. Robot. Syst.* **2018**, *15*. [[CrossRef](#)]
- Pushp, S.; Saikia, A.; Khan, A.; Hazarika, S.M. A cognitively enhanced collaborative control architecture for an intelligent wheelchair: Formalization, implementation and evaluation. *Cogn. Syst. Res.* **2018**, *49*, 114–127. [[CrossRef](#)]
- Ma, K.; Qi, T.Z. A human-centered design of electric wheelchair controller with dual control access for both drivers of disabled people and caregiver. *J. Comput. Inf. Sci. Eng.* **2017**, *17*. [[CrossRef](#)]
- Arnay, R.; Hernández-Aceituno, J.; Toledo, J.; Acosta, L. Laser and Optical Flow Fusion for a Non-Intrusive Obstacle Detection System on an Intelligent Wheelchair. *IEEE Sens. J.* **2018**, *18*, 3799–3805. [[CrossRef](#)]
- Ktistakis, I.P.; Bourbakis, N.G. Assistive intelligent robotic wheelchairs. *IEEE Potentials* **2017**, *36*, 10–13. [[CrossRef](#)]
- Frank, A.O.; De Souza, L.H. Clinical features of children and adults with a muscular dystrophy using powered indoor/outdoor wheelchairs: Disease features, comorbidities and complications of disability. *Disabil. Rehabil.* **2018**, *40*, 1007–1013. [[CrossRef](#)] [[PubMed](#)]
- Kundu, A.S.; Lenka, P.K.; Lenka, P.K.; Bhaumik, S. Design and performance evaluation of 4 wheeled omni wheelchair with reduced slip and vibration. *Procedia Comput. Sci.* **2017**, *105*, 289–295. [[CrossRef](#)]
- Garcia-Mendez, Y.; Pearlman, J.L.; Boninger, M.L.; Cooper, R.A. Health risks of vibration exposure to wheelchair users in the community. *J. Spinal Cord Med.* **2013**, *36*, 365–375. [[CrossRef](#)] [[PubMed](#)]
- Requejo, P.S.; Maneekobkunwong, S.; McNitt-Gray, J. Influence of hand-rim wheelchairs with rear suspension on seat forces and head accelerations during curb descent landings. *J. Rehabil. Med.* **2009**, *41*, 459–466. [[CrossRef](#)] [[PubMed](#)]
- BSI. *BS EN 12183:2009 Manual Wheelchairs-Requirements and Test Methods*; BSI: London, UK, 2009.
- RESNA. *ANSI/RESNA WC-1:2009 Requirements and Test Methods for Wheelchairs (Including Scooters)*; RESNA: Washington, WA, USA, 2009.
- Standardization Administration of China. *GB/T 13800-2009 Manual Wheelchairs*; Standardization Administration of China: Beijing, China, 2009.
- Silva, L.C.; Dedini, F.G.; Corrêa, F.C.; Eckert, J.J.; Becker, M. Measurement of wheelchair contact force with a low cost bench test. *Med. Eng. Phys.* **2015**, *38*, 163–170. [[CrossRef](#)] [[PubMed](#)]
- Hillman, S.J.; Hollington, J.; Crossan, N. Correlation of ISO 16840-2:2007 impact damping and hysteresis measures for a sample of wheelchair seating cushions. *Assist. Technol.* **2018**, *30*, 77–83. [[CrossRef](#)] [[PubMed](#)]
- Wang, S.Y.; Sun, C.Y.; Wang, B.G. Preliminary study on comfortableness of motorized wheelchair cushion. *J. Biomed. Eng.* **2016**, *33*, 320–324.
- Brienza, D.; Valley, J.; Karg, P.; Akins, J.; Gefen, A. An MRI investigation of the effects of user anatomy and wheelchair cushion type on tissue deformation. *J. Tissue Viab.* **2018**, *27*, 42–53. [[CrossRef](#)] [[PubMed](#)]

23. Brown, K.; Flashner, H.; Mcnittgray, J.L. Modeling wheelchair-users undergoing vibrations. *J. Biomech. Eng.* **2017**, *139*. [[CrossRef](#)] [[PubMed](#)]
24. Leary, M.; Gruijters, J.; Mazur, M.; Subic, A.; Burton, M. A fundamental model of quasi-static wheelchair biomechanics. *Med. Eng. Phys.* **2012**, *34*, 1278–1286. [[CrossRef](#)] [[PubMed](#)]
25. Chen, X.Q.; Chase, J.G.; Wolm, P. System Identification and modelling of front wheel drive electric wheelchairs. In Proceedings of the 17th World Congress the International Federation of Automatic Control, Seoul, Korea, 6–11 July 2008.
26. Salipur, Z.; Bertocci, G. Development and validation of rear impact computer simulation model of an adult manual transit wheelchair with a seated occupant. *Med. Eng. Phys.* **2010**, *32*, 66–75. [[CrossRef](#)] [[PubMed](#)]
27. Ceravolo, E.; Gabellone, M.; Farina, M.; Bascetta, L.; Matteucci, M. Model Predictive Control of an autonomous wheelchair. *IFAC PapersOnLine* **2017**, *50*, 9821–9826. [[CrossRef](#)]
28. Dziechciowski, Z.; Kromkaszydek, M. Vibration transmitted to the human body during the patient's ride in a wheelchair. *Arch. Acoust.* **2017**, *42*, 137–148. [[CrossRef](#)]
29. Hikmawan, M.F.; Nugraha, A.S. Analysis of electric wheelchair passenger comfort with a half car model approach. In Proceedings of the 2016 International Conference on Sustainable Energy Engineering and Application: Sustainable Energy for a Better Life, Jakarta, Indonesia, 3–5 October 2016.
30. Miyawaki, K.; Takahashi, D. Investigation of whole-body vibration of passenger sitting on wheelchair and of passenger sitting on wheelchair loaded on lifter. In Proceedings of the 2016 International Symposium on Micro-NanoMechatronics and Human Science, Nagoya, Japan, 28–30 November 2016.
31. Su, K.H.; Chang, T.H.; Su, S.F. Design of fuzzy-based magnetic suspension vibrator for electric wheelchair. In Proceedings of the IEEE 12th International Conference on Networking, Sensing and Control, Taipei, Taiwan, 9–11 April 2015.
32. Ababou, A.; Ababou, N.; Morsi, T.; Boukhechem, L. Test bench for analysis of harmful vibrations induced to wheelchair users. In Proceedings of the Part of 7th International Joint Conference on Biomedical Engineering Systems and Technologies, Angers, France, 3–6 March 2014.
33. Hischke, M.; Raoul, I.I. Effect of rear wheel suspension on tilt-in-space wheelchair shock and vibration attenuation. *PM R* **2018**. [[CrossRef](#)] [[PubMed](#)]
34. Egidio, A.D.; Leo, A.M.D.; Simoneschi, G. Effectiveness of mass–damper dynamic absorber on rocking block under one-sine pulse ground motion. *Int. J. Non-Linear Mech.* **2018**, *98*, 154–162.
35. Orečný, M.; Štefan, S.; Huňady, R.; Želmíra, F. Application of a magneto-rheological damper and a dynamic absorber for a suspension of a working machine seat. *Procedia Eng.* **2014**, *96*, 338–344. [[CrossRef](#)]



© 2018 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).