

Supporting information

A Facile Two-Step Thermal Process for Producing a Dense, Phase-Pure, Cubic Ta-Doped Lithium Lanthanum Zirconium Oxide Electrolyte for Upscaling

Diwakar Karuppiyah ^{1,2,*}, Dmitrii Komissarenko ^{1,3}, Nur Sena Yüzbaşı ¹, Yang Liu ¹,
Pradeep Vallachira Warriam Sasikumar ^{1,4}, Amir Hadian ^{1,5}, Thomas Graule ¹, Frank Clemens ¹
and Gurdial Blugan ^{1,*}

¹ Laboratory for High Performance Ceramics, Empa, Swiss Federal Laboratories for Materials Science and Technology, CH-8600 Duebendorf, Switzerland;
dmitrii.komissarenko@fhnw.ch (D.K.); sena.yuezbaşı@empa.ch (N.S.Y.);
pradeep.warriam@advano.io (P.V.W.S.); amir.hadian@fhnw.ch (A.H.);
thomas.graule@empa.ch (T.G.); frank.clemens@empa.ch (F.C.)

² Department of Mechanical Engineering Applied Mechanics, University of Pennsylvania, Philadelphia, PA 19104, USA

³ Institute for Biomass and Resource Efficiency, University of Applied Sciences and Arts Northwestern Switzerland (FHNW), 5210 Windisch, Switzerland

⁴ ADVANO, Lakeshore Drive, New Orleans, LA 70112, USA

⁵ Institute of Product and Production Engineering, University of Applied Sciences and Arts Northwestern Switzerland (FHNW), 5210 Windisch, Switzerland

* Correspondence: diwakark@seas.upenn.edu (D.K.); gurdial.blugan@empa.ch (G.B.)




Figure S1 Schematic representation of the experimental process of Ta:LLZO.




Figure S2(a-d) TG and DTA of wet milled La_2O_3 , Ta_2O_5 , ZrO_2 and Li_2CO_3 powder.