

Supporting information for

Ion conductance-based perfusability assay of vascular vessel models in microfluidic devices

Rise Akasaka¹, Masashi Ozawa², Yuji Nashimoto^{2,3}, Kosuke Ino^{2,*}, Hitoshi Shiku^{2,*}

¹ Graduate School of Environmental Studies, Tohoku University, 6-6-11 Aramaki-aza Aoba, Aoba-ku, Sendai 980-8579, Japan

² Graduate School of Engineering, Tohoku University, 6-6-11 Aramaki-aza Aoba, Aoba-ku, Sendai 980-8579, Japan

³ Frontier Research Institute for Interdisciplinary Sciences, Tohoku University, 6-3 Aramaki-aza Aoba, Aoba-ku, Sendai 980-8578, Japan

Corresponding authors: Kosuke Ino (kosuke.ino@tohoku.ac.jp) and Hitoshi Shiku (hitoshi.shiku.c3@tohoku.ac.jp)

Table of Contents

- Figure S1
- Figure S2




Figure S1

Device dimensions. (A) Overview. (B) Detailed information. The heights of all the channels were 100 μm . (C) Device photograph.




Figure S2

Device during the measurements. (A) Illustration. WE: working electrode. CE: counter electrode. RE: reference electrode. (B) Photograph.