

Support Information

Article

Stability Improvement of Perovskite Solar Cells by the Moisture-Resistant PMMA:Spiro-OMeTAD Hole Transport Layer

Shaohua Ma ^{1,†}, Shangzheng Pang ^{2,†}, Hang Dong ², Xiaoping Xie ³, Gang Liu ³, Peng Dong ³, Dawei Liu ³, Weidong Zhu ², He Xi ², Dazheng Chen ^{2,*}, Chunfu Zhang ^{2,*} and Yue Hao ²

¹ Key Laboratory of Micro/Nano Systems for Aerospace, Ministry of Education, Northwestern Polytechnical University, Xi'an 710072, China; mashaohua@spic.com.cn

² Wide Bandgap Semiconductor Technology Disciplines State Key Laboratory, Shaanxi Joint Key Laboratory of Graphene, School of Microelectronics, Xidian University, Xi'an 710071, China; szpang@stu.xidian.edu.cn (S.P.); donghangxd@163.com (H.D.); wdzhu@xidian.edu.cn (W.Z.); hxi@xidian.edu.cn (H.X.); yhao@xidian.edu.cn (Y.H.)

³ Qinghai Huanghe Hydropower Development Co., Ltd., Xining 810008, China; xiexiaoping@spic.com.cn (X.X.); liugang@spic.com.cn (G.L.); dongpeng@spic.com.cn (P.D.); liudawei02@spic.com.cn (D.L.)

* Correspondence: dzchen@xidian.edu.cn (D.C.); cfzhang@xidian.edu.cn (C.Z.)

† These authors contributed equally to this work.




Figure S1. JV curves of PSCs stored for a long time of (a) pure spiro-OMeTAD and (b) PMMA (2 mg/mL): spiro-OMeTAD based cells kept in the air atmosphere at RH = 40% for 80 days.




Figure S2. The procedures of renovating long-term stored PSCs. The gray layer represents the Ag electrode, the purple layer represents the spiro-OMeTAD and the orange layer represents perovskite and other support layers.